

(项目名称)

灯具图片		日期																	
Lighting Description		Date																	
图片仅供参考, 以实物颜色外观为准! 		品牌	IG																
		Brand																	
		编号	导轨式射灯																
		Number																	
		灯具名称	IG-DG506012 01																
		Description																	
		灯具型号	IG-DG506012 01																
		Model																	
		应用位置																	
		Applied position																	
数量																			
Quantity																			
灯具/Fixture		配光曲线/Lighting Distribution																	
产地	中国	 <table border="1" style="display: inline-table; margin-left: 20px;"> <thead> <tr> <th>h(m)</th> <th>D(cm)</th> <th>E(lx)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>67</td> <td>1433</td> </tr> <tr> <td>2</td> <td>134</td> <td>358</td> </tr> <tr> <td>3</td> <td>201</td> <td>159</td> </tr> <tr> <td>4</td> <td>269</td> <td>90</td> </tr> </tbody> </table>			h(m)	D(cm)	E(lx)	1	67	1433	2	134	358	3	201	159	4	269	90
h(m)	D(cm)				E(lx)														
1	67				1433														
2	134				358														
3	201				159														
4	269				90														
材质	铝																		
颜色	白/黑																		
反光罩																			
输入电压	220V																		
光通量	780lm																		
防护等级	IP20																		
安装方式	导轨式																		
尺寸	Φ 60*165mm/Φ 60*125mm																		
开孔尺寸	2 线/3 线/4 线																		
光源/Lighting Resource		灯具尺寸/Fixture Size																	
品牌/类型	LED COB																		
功率	12W																		
光束角	36°																		
色温	3000K/4000K																		
显色指数	RA>90																		
平均寿命	30000H																		
电器/Electrical Equipment					附件/Accessories														
品牌/类型	LED 恒流驱动	 防眩蜂窝网片																	
控制方式	开关、0/1-10V、DALI																		
输入电压	220V																		
功率因数	0.5																		
平均寿命	30000H																		
Supplier	Contact	TEL	Design No																
供货商: 广东爱奇光电科技有限公司	联络人:	电话:	设计编码:																
Remarks 备注: 1. 材料颜色以实际样板为主, 材料须保证品质并符合大量施工需要; 2. 承建商应提供实物样板供设计师认可; 3. 承建商必须提前预测材料定货期事宜; 4. 如需替换同类其它品牌材料, 需承建方提供同类品牌样品供设计方重新确定。																			